

LOC/DME I-OGG	APP CRS	Rwy Idg	6995
110.1	024°	TDZE	55
Chan 38		Apt Elev	55

ILS Y or LOC Y RWY 2
KAHULUI (OGG)(PHOG)

DME required.

▼


▲

For inop ALS, increase S-ILS 2 Cat E visibility to ¾ SM, and S-LOC 2 Cats C/D/E visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 3000 on OGG VORTAC R-023 to KRANE/OGG 13 DME and hold.

ATIS	HCF APPROACH	MAUI TOWER ★	GND CON	CLNC DEL	UNICOM
128.6	120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	118.7 (CTAF) 0 279.6	121.9 279.6	120.6 290.5	122.95



Use I-OGG DME when on the localizer course. VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 77).

One Minute Holding Pattern

CAMPS I-OGG 17.7

TEBBS I-OGG 8.5

NOWAK I-OGG 4.8

OGG R-023

KRANE OGG 13

14000

3000

204°

024°

2400

1220

9.2 NM

3.7 NM


2.3 NM

1.2

GS 3.00°

TCH 62

CATEGORY	A	B	C	D	E
S-ILS 2	275-½ 220 (300-½)				
S-LOC 2	520-½ 465 (500-½)		520-1 465 (500-1)		
CIRCLING	520-1 465 (500-1)	620-1 565 (600-1)	740-2 685 (700-2)	1140-3 1085 (1100-3)	1720-3 1665 (1700-3)



PAC, 07 AUG 2025 to 02 OCT 2025

PAC, 07 AUG 2025 to 02 OCT 2025