

ATLANTA, GEORGIA

AL-26 (FAA)

25219


LOC/DME I-BRU <b>108.7</b> Chan <b>24</b>	APP CRS <b>275°</b>	Rwy Ldg 9999 8500 TDZE 996 990 Apt Elev <b>1026 1026</b>
---	------------------------	---

# ILS or LOC RWY 26L

HARTSFIELD/JACKSON ATLANTA INTL (ATL)




**RADAR required.**

▼ Inop table does not apply to sidestep Rwy 26R Cats A and B. For inop ALS, increase S-ILS 26L all Cats visibility to RVR 4500 and S-LOC 26L Cat E visibility to RVR 6000. For inop ALS to Rwy 26R, increase sidestep 26R Cat E visibility to 2 SM. Simultaneous approach authorized.





MISSED APPROACH: Climb to 1500 then climbing right turn to 4000 on heading 290° and RMG R-132 to DALAS INT/RMG VORTAC 18.5 DME and hold.

D-ATIS ARR <b>119.65</b>	ATLANTA APP CON	ATLANTA TOWER					ALL RWYS	GND CON	ALL RWYS
DEP <b>125.55</b>	<b>127.9</b> <b>379.9</b>	<b>119.1</b>	<b>125.325</b>	<b>123.85</b>	<b>119.3</b>	<b>119.5</b>	<b>254.4</b>	<b>121.9</b>	<b>121.75</b> <b>121.65</b> <b>254.4</b>



ELEV 1026	<b>D</b> TDZE 26L 996 TDZE 26R 990
-----------	---------------------------------------



FAF to MAP 4.2 NM	HIRL all Rwy's TDZ/CL Rwy's 8L, 9R, 10, 26R, 27L and 28				
Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24
CATEGORY	A	B	C	D	E
S-ILS 26L	1280/24 284 (300-1/2)				
S-LOC 26L	1380/24	384 (400-1/2)	1380/35	384 (400-3/4)	
SIDESTEP 26R	1380/55 390 (400-1)			1380-1 1/2 390 (400-1 1/2)	

ATLANTA, GEORGIA  
Amdt 22 22APR21

33°38'N-84°26'W

# HARTSFIELD/JACKSON ATLANTA INTL (ATL) ILS or LOC RWY 26L

SE-4, 19 FEB 2026 to 19 MAR 2026

SE-4, 19 FEB 2026 to 19 MAR 2026

ATLANTA, GEORGIA

AL-26 (FAA)

26078


LOC/DME I-BRU <b>108.7</b> Chan 24	APP CRS <b>275°</b>	Rwy Ldg 9999 8500 TDZE 996 990 Apt Elev 1026 1026
--	------------------------	--

# ILS or LOC RWY 26L

HARTSFIELD/JACKSON ATLANTA INTL (ATL)




**RADAR required.**

▼ Inop table does not apply to sidestep Rwy 26R Cats A and B. For inop ALS, increase S-ILS 26L all Cats visibility to RVR 4500 and S-LOC 26L Cat E visibility to RVR 6000. For inop ALS to Rwy 26R, increase sidestep 26R Cat E visibility to 2 SM. Simultaneous approach authorized.





**MISSED APPROACH:** Climb to 1500 then climbing right turn to 4000 on heading 290° and RMG R-132 to DALAS INT/RMG VORTAC 18.5 DME and hold.

D-ATIS <b>119.65</b>	ATLANTA APP CON <b>127.9 379.9</b>	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS <b>119.1 125.325 123.85 119.3 119.5 254.4</b>				ALL RWYS <b>121.9</b>	GND CON ALL 8L-26R, 8R-26L 9L-27R, 9R-27L 10-28 RWYS <b>121.75 121.65 254.4</b>
-------------------------	---------------------------------------	--	--	--	--	--------------------------	---



ELEV 1026	<b>D</b> TDZE 26L 996 TDZE 26R 990
-----------	---------------------------------------



FAF to MAP 4.2 NM	HIRL all Rwy's TDZL/RCLS Rwy's 8L, 9R, 10, 26R, 27L and 28				
Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24
CATEGORY	A	B	C	D	E
S-ILS 26L	1280/24 284 (300-1/2)				
S-LOC 26L	1380/24	384 (400-1/2)	1380/35	384 (400-3/4)	
SIDESTEP 26R	1380/55 390 (400-1)			1380-1 1/2 390 (400-1 1/2)	

ATLANTA, GEORGIA  
Amdt 22 22APR21

HARTSFIELD/JACKSON ATLANTA INTL (ATL)  
33°38'N-84°26'W  
**ILS or LOC RWY 26L**

SE-4, 19 MAR 2026 to 16 APR 2026

SE-4, 19 MAR 2026 to 16 APR 2026