

ATLANTA, GEORGIA

AL-26 (FAA)

25219

WAAS CH <b>40399</b> <b>W10A</b>	APP CRS <b>095°</b>	Rwy Ldg TDZE <b>1000</b> Apt Elev <b>1026</b>
--	------------------------	---

# RNAV (GPS) Y RWY 10

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME-0.3 RNP NA. For inop ALSF-2, increase LNAV/VNAV all Cats visibility to 1½ mile and LNAV Cats C and D visibility to 1¾ mile. LNAV procedure NA during simultaneous operations. Simultaneous approach authorized with Rwy 8L or 8R or 9L, or Rwys 8L and 9L. Use of FD or AP providing RNAV track guidance required during simultaneous operations.






MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SCARR and hold.



D-ATIS ARR <b>119.65</b> DEP <b>125.55</b>	ATLANTA APP CON <b>127.9 379.9</b>	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS <b>119.1 125.325 123.85 119.3 119.5 254.4</b>				ALL RWYS <b>121.9</b>	GND CON (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 RWYS <b>121.75 121.65 254.4</b>	ALL RWYS <b>121.9</b>
--	--	--	--	--	--	-----------------------------	---	-----------------------------

## RADAR REQUIRED

CLNC DEL	CPDLC
<b>118.1</b>	



ELEV 1026	TDZE 1000
-----------	-----------



CATEGORY	A	B	C	D
LPV DA		1200/18	200 (200-½)	
LNAV/VNAV DA		1455/55	455 (500-1)	
LNAV MDA	1480/24	480 (500-½)	1480/50	480 (500-1)

HIRL all Rwys  
TDZ/CL Rwys 8L, 9R, 10, 26R,  
27L and 28

ATLANTA, GEORGIA  
Amdt 4A 12OCT17

33°38'N-84°26'W

# RNAV (GPS) Y RWY 10

SE-4, 19 FEB 2026 to 19 MAR 2026

SE-4, 19 FEB 2026 to 19 MAR 2026

ATLANTA, GEORGIA

AL-26 (FAA)

26078

WAAS CH <b>40399</b> <b>W10A</b>	APP CRS <b>095°</b>	Rwy Ldg TDZE <b>1000</b> Apt Elev <b>1026</b>
--	------------------------	---

# RNAV (GPS) Y RWY 10

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME-0.3 RNP NA. For inop ALSF-2, increase LNAV/VNAV all Cats visibility to 1½ mile and LNAV Cats C and D visibility to 1¾ mile. LNAV procedure NA during simultaneous operations. Simultaneous approach authorized with Rwy 8L or 8R or 9L, or Rwys 8L and 9L. Use of FD or AP providing RNAV track guidance required during simultaneous operations.




ALSF-2



MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SCARR and hold.

D-ATIS <b>119.65</b>	ATLANTA APP CON <b>127.9 379.9</b>	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS <b>119.1 125.325 123.85 119.3 119.5 254.4</b>				ALL RWYS <b>121.9</b>	GND CON (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 RWYS <b>121.75 121.65 254.4</b>
-------------------------	---------------------------------------	--	--	--	--	--------------------------	---



## RADAR REQUIRED



SE-4, 19 MAR 2026 to 16 APR 2026

SE-4, 19 MAR 2026 to 16 APR 2026

ELEV 1026 TDZE 1000



CATEGORY	A	B	C	D
LPV DA		1200/18	200 (200-½)	
LNAV/VNAV DA		1455/55	455 (500-1)	
LNAV MDA	1480/24	480 (500-½)	1480/50	480 (500-1)

HIRL all Rwys  
TDZL/RCLS Rwys 8L, 9R, 10, 26R, 27L and 28

ATLANTA, GEORGIA  
Amdt 4A 12OCT17

33°38'N-84°26'W

# HARTSFIELD/JACKSON ATLANTA INTL (ATL) RNAV (GPS) Y RWY 10