


ZELAN FOUR DEPARTURE (RNAV)

**TOP ALTITUDE:
10000**

D-ATIS 125.55
 CLNC DEL 118.1
 CPDLC
 GND CON
 121.9 254.4 (Rwys 8L-26R, 8R-26L)
 121.75 254.4 (Rwys 9L-27R, 9R-27L)
 121.65 254.4 (Rwy 10-28)
 ATLANTA TOWER
 119.1 254.4 (Rwy 8L-26R)
 125.325 254.4 (Rwy 8R-26L)
 119.3 254.4 (Rwy 9R-27L)
 123.85 254.4 (Rwy 9L-27R)
 119.5 254.4 (Rwy 10-28)

ATLANTA DEP CON
 133.475 281.425 (Rwys 8L-26R, 8R-26L)
 125.65 281.425 (Rwys 9L-27R, 9R-27L)
 121.225 281.425 (Rwy 10-28)



- NOTE: For turbojets only.
- NOTE: RNP-1.
- NOTE: RF required.
- NOTE: GPS required.
- NOTE: If unable to accept climb rate, advise clearance delivery on initial contact.
- NOTE: Use departure frequency depicted unless otherwise assigned.
- NOTE: Accelerate to 250K, if unable, advise both tower and departure control on initial contact.
- NOTE: Transponder code will be issued via PDC or Atlanta clearance delivery.
- NOTE: Aircraft at midfield ramps will advise ramp towers of departure SID prior to pushback. Upon receipt of ATC clearance (from ATL clearance delivery), readback only your call sign and transponder code, unless you have a question.

TAKEOFF MINIMUMS
 Rwy 27R: Standard with minimum climb of 500' per NM to 1527.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

ZELAN FOUR DEPARTURE (RNAV)

SE-4, 14 MAY 2026 to 11 JUN 2026

SE-4, 14 MAY 2026 to 11 JUN 2026



DEPARTURE ROUTE DESCRIPTION
SEE ADDITIONAL REQUIREMENTS ON AAUP

TAKEOFF RWY 27R: Climb on course 275° to CPARK, then right turn to MPASS, then on track 006° to cross ZELAN at or above 6000. Maintain 250K until ZELAN. Thence

. . . . on assigned enroute transition. Maintain 10000 (or filed altitude, if lower): Expect clearance to filed altitude ten minutes after departure.

BOBBD TRANSITION (ZELAN4.BOBBD)

EMAHH TRANSITION (ZELAN4.EMAHH)

GLAZR TRANSITION (ZELAN4.GLAZR)

JAACE TRANSITION (ZELAN4.JAACE)

RAFTN TRANSITION (ZELAN4.RAFTN)

RESPE TRANSITION (ZELAN4.RESPE)

SMTTH TRANSITION (ZELAN4.SMTTH)

SE-4, 14 MAY 2026 to 11 JUN 2026

SE-4, 14 MAY 2026 to 11 JUN 2026