
SANTA BARBARA DEP CON
120.55 319.15
ATIS
132.65
CLNC DEL
132.9
GND CON
121.7
SANTA BARBARA TOWER ★
119.7 254.35
TOP ALTITUDE: ASSIGNED BY ATC
RNAV 1 - DME/DME/IRU or GPS.
RADAR required for non-GPS equipped aircraft.
TAKEOFF MINIMUMS
Rwys 33L/R: NA, Environmental.
Rwys 15L: Standard.
Rwys 7, 25: Standard with minimum climb of 500'/NM to 520.
Rwy 15R: 300-1.
NNAVY
BOILE
10000
10000
*9400
062°
(55)
10000
*10000
150°
(7)
CAMARILLO
CMA
IKAYE
5500
*4100
105°
(8)
LYTTL
064°
(24)
5500
*2900
KPTIN
(111)
5500
*2300
057°
064°
5500
*2500
(21)
MISHN
133°
(15)
119°
(17)
085°
(16)
124°
EFFRM
JEHTT
075°
255°
193°
WNFRY
145°
(11)
DNKYY
MSA SBA 25 NM
8300
N
SANTA CATALINA
SXC
5500
*4400
114°
(73)
NOTE: Turbojets and turboprops only.
NOTE: KPTIN Transition restricted to aircraft landing KLAX and KHHR.
NOTE: IKAYE Transition is ATC assigned only.
NOTE: Chart not to scale.
DEPARTURE ROUTE DESCRIPTION
TAKEOFF RUNWAY 7: Climb on heading 075° to intercept course 124° to EFFRM, then on track 133° to MISHN, thence. . . .
TAKEOFF RUNWAYS 15L/R: Climb direct JEHTT, then on track 119° to MISHN, thence. . . .
TAKEOFF RUNWAY 25: Climb on heading 255° to intercept course 193° to WNFRY, then on track 145° to DNKYY, then on track 085° to MISHN, thence. . . .
. . . on (transition). Maintain ATC assigned altitude. Expect final altitude 10 minutes after departure.
BOILE TRANSITION (MISHN5.BOILE)
IKAYE TRANSITION (MISHN5.IKAYE)
KPTIN TRANSITION (MISHN5.KPTIN)
NNAVY TRANSITION (MISHN5.NNAVY)
SANTA CATALINA TRANSITION (MISHN5.SXC)