

RADAR MINS

26134

N1

RADAR INSTRUMENT APPROACH MINIMUMS

CAMP PENDLETON MCAS (MUNN FLD) (KNFG)

Oceanside, CA Amdt 6 14MAY26 (26134) (USN)

RADAR - (E) 236.3 277.325 **▽ ▲** NA

ELEV 78

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR †	21 ^{1 2 3 4 5}	3.6°/53/889	ABCD	388-¾	310	(400-¾)
ASR	21 ^{6 7 8 9}		AB CD	960-1 960-2½	882 882	(900-1) (900-2½)
CIR	All Rwy ^{10 11}		A B CD	1020-1¼ 1260-1½ 1480-3	942 1182 1402	(1000-1¼) (1200-1½) (1500-3)

†CAUTION: Missed Approach
Minimum Climb Rate to 1500

Knots	60	120	180	240	300	360
V/V (fpm)	299	598	897	1196	1495	1794

¹ CAUTION - Trees penetrate 34:1 visual obstacle surfaces approximately 2300' from threshold, 500' left of cntrln. Pilots must have trees in sight prior to descending from DA/MDA.

² When ALS inop, increase CAT ABCD vis to ¾ mile.

³ No-NOTAM preventative maint sked: PAR 2100-0100Z++ Mon.

⁴ Helicopter visibility reduction below ¾ NM not authorized.

⁵ CAUTION: GP exceeds maximum for CAT D (3.5°)

⁶ Step Down Fix altitude(s) are less than circling CAT BCD MDA.

⁷ When ALS inop, increase CAT AB vis to 1¼ miles.

⁸ Step Down Fix at 3NM from thld, 1240 min.

⁹ Step Down Fix at 4.5NM from thld, 1800 min.

¹⁰ Circling authorized from ASR only.

¹¹ Circling to Rwy 3 not authorized at night when PAPI OTS.

11 JUN 2026 to 09 JUL 2026

11 JUN 2026 to 09 JUL 2026

SW-3

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26134

N1

RADAR MINS


26134

N2

RADAR INSTRUMENT APPROACH MINIMUMS

MIRAMAR MCAS (JOE FOSS FLD) (KNKX)

San Diego, CA Amdt 3 22JAN26 (26022) (USN)

RADAR¹ - (E) 133.625 134.3x 266.8x 270.35 307.9x 328.4x 348.75 350.275 371.9 379.125 

ELEV 477

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	24R ² 24L	3.2°/57/1130 3.2°/49/1022	ABCDE ABCDE	897-¾ 727-¾	422 250	(500-¾) (300-¾)
PAR W/O GS	24R ^{3,4} 24L ⁴		AB CDE AB CDE	1000-½ 1000-1 1000-1 1000-1½	525 525 523 523	(600-½) (600-1) (600-1) (600-1½)
ASR Z	6L ⁵		AB CDE	820-1 820-1½	388 388	(400-1) (400-1½)
ASR	24R ^{6,7} 24L ⁷		AB CDE AB CDE	960-½ 960-1 940-1 940-1½	485 485 463 463	(500-½) (500-1) (500-1) (500-1½)
ASR Y	6L		AB CDE	1140-1 1140-2	708 708	(700-1) (700-2)
CIR ^{8,9}	All Rwy		AB C DE	1120-1 1300-2½ 1500-3	643 823 1023	(700-1) (900-2½) (1100-3)
CIR ⁸ (ASR Y)	6L		AB C DE	1140-1 1300-2½ 1500-3	663 823 1023	(700-1) (900-2½) (1100-3)

¹Other APP CON freq as assigned.

²When ALS inop, increase vis to 1¼ miles.

³When ALS inop, increase CAT AB vis to 1 mile; CAT CDE vis to 1½ miles.

⁴Step Down Fix at 3 NM from RPI, 1500 min, Step Down Fix at 2 NM from RPI, 1160 min.

⁵Step Down Fix at 2 NM from thld, 1140 min.

⁶When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.

⁷Step Down Fix at 3 NM from thld, 1600 min, Step Down Fix at 2 NM from thld, 1240 min.

⁸Circling not authorized SE of Rwy 6R-24L.

⁹All RADAR procedures except ASR Y Rwy 6L.

Missed Approach Minimum Climb Rate of 240 ft/NM to 3900

Rwy	Knots	60	120	180	240	300	360
ASR Z 6L	V/V (fpm)	240	480	720	960	1200	1440

11 JUN 2026 to 09 JUL 2026

11 JUN 2026 to 09 JUL 2026

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26134

N2

SW-3

RADAR INSTRUMENT APPROACH MINIMUMS

NORTH ISLAND NAS (HALSEY FIELD) (KNZY)

San Diego, CA Amdt 2 04SEP25 (25247) (USN)

ELEV 26

RADAR - (E) 127.7x 133.175x 318.8x 360.8x 353.5x 382.0x 385.5x **▽**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAT_h</u>	<u>CEIL-VIS</u>
PAR ¹	36 ^{2,3}	3.0°/46/856	ABCD	119-¼	100	(100-¼)
	29 ⁴	3.0°/46/944	ABCDE	276-½	250	(300-½)
PAR W/O GS ¹	36 ⁵		AB	460-¾	441	(500-¾)
			CDE	460-1	441	(500-1)
	29 ^{6,7}		AB	560-¾	534	(600-¾)
			CDE	560-1	534	(600-1)
PAR SHORT OFFSET	29 ^{18,9}	3.0°/46/944	A	620-2	594	(600-2)
PAR OFFSET	29 ^{1,9}	3.0°/46/944	ABCDE	620-2	594	(600-2)
PAR WO GS OFFSET	29 ^{1,7,9}		ABCDE	620-2	594	(600-2)
ASR	29 ^{5,7}		AB	540-½	514	(600-½)
			CDE	540-1	514	(600-1)
	36 ¹⁰		A	800-¾	781	(800-¾)
			B	800-1	781	(800-1)
			CDE	800-2	781	(800-2)
ASR OFFSET	29 ^{7,9}		ABCDE	620-2	594	(600-2)
CIR	29 ⁷		AB	620-2	594	(600-2)
			CDE	NOT AUTHORIZED		
	36		ABCDE	NOT AUTHORIZED		

11 JUN 2026 to 09 JUL 2026

11 JUN 2026 to 09 JUL 2026

¹No-NOTAM MP sked 2000-2400Z++ Mon.

²When ALS inop, increase vis to ½ mile.

³CAT E aircraft NOT AUTHORIZED.

⁴When ALS inop, increase vis to ¾ mile.

⁵When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1 ¾ miles.

⁶When ALS inop, increase CAT AB vis to 1 mile, CAT CDE to 1 ½ miles.

⁷Cir auth to Rwy 18 only. Cir not auth W Rwy 18-36.

⁸Minima applicable for rotorcraft short offset approaches.

⁹Final apch crs 299° offset 8° from RCL 291°.

¹⁰When ALS inop, increase CAT A vis to 1 mile, CAT B to 1 ¼ miles, CAT CDE vis to 2 ½ miles.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

POINT MUGU NAS (NAVAL BASE VENTURA CO) (KNTD)

Oxnard, CA Amdt 3 04SEP25 (25247) (USN)

ELEV 13

RADAR¹ - (E) 123.75x 133.25 233.7x 269.225 350.25 353.925 **▽**

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/HATH/ HAA</u>	<u>CEIL-VIS</u>
PAR	3 ²	3.0°/46/873	ABCDE	110 - ³ / ₄	100	(100- ³ / ₄)
	21	3.0°/47/892	ABCDE	113 - ³ / ₂	100	(100- ³ / ₂)
ASR	3 ^{3,4}		ABCDE	380 - ³ / ₄	370	(400- ³ / ₄)
	21 ^{5,6}		AB	420 - ¹ / ₂	407	(500- ¹ / ₂)
			CDE	420 - ³ / ₄	407	(500- ³ / ₄)
CIR ^{7,8}	3, 21		A	420 -1	470	(500-1)
			B	520 -1	507	(600-1)
			C	520 -1 ¹ / ₂	507	(600-1 ¹ / ₂)
			D	580 -2	567	(600-2)
			E	NOT AUTHORIZED		

Expanded RADAR svc-All flt conducted under positive ctl. Inbd acft not opr under ATC or PLEAD ctc APP CON 25 NM out on 307.275 or 128.65.

¹No-NOTAM preventive maint 1500-2000Z++ Tue.

²When ALS inop, increase vis to ¹/₂ mile.

³When ALS inop, increase vis to 1 mile.

⁴Step down fix at 2 NM from thld, 700 min.

⁵When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¹/₂ miles.

⁶Step down fix at 4 NM from thld, 1400 min, 3 NM from thld, 1080 min.

⁷CAT A remain within 1.3 NM, CAT B remain within 1.5 NM, CAT C remain within 1.7 NM, CAT D remain within 2.3 NM.

⁸Circling not authorized SE of Rwy 3-21.

11 JUN 2026 to 09 JUL 2026

11 JUN 2026 to 09 JUL 2026

RADAR INSTRUMENT APPROACH MINIMUMS