

ATLANTA, GEORGIA

AL-26 (FAA)

26078

WAAS CH 65700 W27A	APP CRS 275°	Rwy Ldg TDZE 999 Apt Elev 1026
--	------------------------	--

RNAV (GPS) RWY 27L




HARTSFIELD/JACKSON ATLANTA INTL (ATL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 26R or 26L. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.




MISSED APPROACH: Climb to 4000 direct CALUP and on track 272° to TEMPO and hold.

D-ATIS	ATLANTA APP CON	ATLANTA TOWER				ALL RWYS	GND CON	ALL RWYS
119.65	127.9 379.9	8L-26R	8R-26L	9L-27R	9R-27L	10-28	(8L-26R, 8R-26L) (9L-27R, 9R-27L) 10-28	121.75 121.65 254.4
		119.1	125.325	123.85	119.3	119.5 254.4	121.9	



ELEV 1026	D	TDZE 999
------------------	----------	-----------------

RADAR REQUIRED



4000	CALUP	tr 272°	TEMPO	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 79).					SLVAA
*LNAV only.				DEPOT	GRMPI	SEJAY	ROMMM	275°	7000
RW27L				*1.7 NM to RW27L	2800	4000	5000	6000	GP 3.00° TCH 58
1.7 NM				3.8 NM	4.7 NM	3.8 NM	3.5 NM	3.5 NM	
CATEGORY		A		B		C		D	
LPV	DA	1199/18		200 (200-½)					
LNAV/ VNAV	DA	1528-1⅓		529 (600-1⅓)					
LNAV	MDA	1620/24	621 (600-½)	1620-1⅓		621 (600-1⅓)			

HIRL all Rws
TDZL/RCLS Rws 8L,
9R, 10, 26R, 27L and 28

ATLANTA, GEORGIA
Amdt 5A 12OCT17

HARTSFIELD/JACKSON ATLANTA INTL (ATL)
33°38'N-84°26'W
RNAV (GPS) RWY 27L

SE-4, 11 JUN 2026 to 09 JUL 2026

SE-4, 11 JUN 2026 to 09 JUL 2026

ATLANTA, GEORGIA

AL-26 (FAA)

26190

WAAS CH 65700 W27A	APP CRS 275°	Rwy Ldg TDZE 999 Apt Elev 1026
--	------------------------	--

RNAV (GPS) RWY 27L




HARTSFIELD/JACKSON ATLANTA INTL (ATL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 26R or 26L. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.


ALSF-2

MISSED APPROACH: Climb to 4000 direct CALUP and on track 272° to TEMPO and hold.

D-ATIS	ATLANTA APP CON	ATLANTA TOWER					ALL RWYS	GND CON			ALL RWYS
119.65	134.725 379.9	8L-26R	8R-26L	9L-27R	9R-27L	10-28	119.1 125.325 123.85 119.3 119.5 254.4	(8L-26R,8R-26L)	(9L-27R,9R-27L)	10-28	121.9 121.75 121.65 254.4



ELEV 1026	D	TDZE 999
------------------	----------	-----------------



HIRL all Rwys
TDZL/RCLS Rwys 8L,
9R, 10, 26R, 27L and 28

RADAR REQUIRED

4000	CALUP	tr 272°	TEMPO	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 79).					SLVAA
*LNAV only.				DEPOT	GRMPI	SEJAY	ROMMM	275°	7000
RW27L				*1.7 NM to RW27L 2800	2800	4000	5000	6000	GP 3.00° TCH 58
→ 1.7 NM				3.8 NM	4.7 NM	3.8 NM	3.5 NM	3.5 NM	
CATEGORY	A		B		C		D		
LPV DA			1199/18		200 (200-½)				
LNAV/ VNAV DA			1528-1⅓		529 (600-1⅓)				
LNAV MDA	1620/24		621 (600-½)		1620-1⅓		621 (600-1⅓)		

ATLANTA, GEORGIA

Amdt 5A 12OCT17

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

33°38'N-84°26'W

RNAV (GPS) RWY 27L

SE-4: 09 JUL 2026 to 06 AUG 2026

SE-4: 09 JUL 2026 to 06 AUG 2026