

APP CRS
016°

Rwy Ldg
TDZE
Apt Elev
5700
56
56

RNAV (RNP) Z RWY 2L
JOHN WAYNE/ORANGE COUNTY (SNA)


RNP AR APCH - GPS. Authorization required. From OSOYI: RF.

▼

For uncompensated Baro-VNAV systems, procedure NA below 5°C or above 54°C.

MISSED APPROACH: Climb to 800 then climbing left turn to 2600 direct SLI VORTAC and hold.

D-ATIS 126.0	SOCAL APP CON 121.3 263.1	JOHN WAYNE TOWER ★ 126.8 (CTAF) 0 343.625	GND CON 120.8	UNICOM 122.95
------------------------	-------------------------------------	--	-------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).

800 2600 SLI

NEWPO 1600

1600 016°

GP 3.00° TCH 55

See planview for multiple IF locations.

4.7 NM

RW02L

CATEGORY A B C D

RNP 0.30 DA 403-1 3/8 347 (400-1 1/8)

AUTHORIZATION REQUIRED

ELEV 56 TDZE 56

REIL Rwy 20L
MIRL Rwy 2R-20L
HIRL Rwy 2L-20R