

VOR RWY 6

VORTAC BZA 116.8 Chan 115	APCH CRS 048°	Rwy Idg TDZE 387 Arpt Elev 433	[USA] LAGUNA AAF (YUMA PROVING GROUND) (KLGFB)
--	--------------------------------	---	---

RADAR required for holding.

▲ * Procedure not authorized at night.
▲▲ NA ** Circling not authorized NW of rwy 06 and 18.

ATIS 128.225	YUMA APP CON 124.7 371.975	TOWER ★ 126.2 (CTAF) 242.175	GND CON 121.8 229.4
-------------------------------	---	---	--------------------------------------

Helicopter visibility reduction not authorized.

Procedure not authorized when airfield closed.

Unlit road 379' MSL, 314' from threshold.

Obtain local altimeter setting on CTAF.
When not received, use Yuma MCAS Intl altimeter setting.

UNITED STATES
MEXICO

3800 BZA

↑ 1400 when using Yuma MCAS Intl altimeter setting

BZA 11.6

5.6 NM 6 NM

CATEGORY	A	B	C	D
S-6*	1320-1¼ 933 (900-1¼)		1320-2½ 933 (900-2½)	
CIRCLING**	1320-1¼ 887 (900-1¼)		1320-2¾ 887 (900-2¾)	1320-3 887 (900-3)
DME MINIMA				
S-6*	1040-1 653 (700-1)		1040-1⅞ 653 (700-1⅞)	
CIRCLING**	1080-1 647 (700-1)		1080-1⅞ 647 (700-1⅞)	1080-2 647 (700-2)
YUMA MCAS/YUMA Intl ALTIMETER SETTING				
S-6*	1400-1¼ 1013 (1000-1¼)	1400-1½ 1013 (1000-1½)	1400-3 1013 (1000-3)	
CIRCLING**	1400-1¼ 967 (1000-1¼)	1400-1½ 967 (1000-1½)	1400-3 967 (1000-3)	
YUMA MCAS/YUMA Intl ALTIMETER SETTING DME MINIMA				
S-6*	1120-1 733 (700-1)		1120-2 733 (700-2)	
CIRCLING**	1160-1 727 (800-1)		1160-2 727 (800-2)	1160-2¼ 727 (800-2¼)

2674

ELEV 433 TDZE 387

MIRL Rwy 18-36					
FAF to MAP 11.6 NM					
Knots	60	90	120	150	180
Min:Sec	11:36	7:44	5:48	4:38	3:52