

WAAS
CH 97400
W09B

APP CRS
095°

Rwy Ldg
TDZE 1026
Apt Elev 1026

RNAV (GPS) RWY 9R

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 8L or 8R. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSIF-2

MISSED APPROACH: Climb to 4000 direct RATCH and on track 092° to CONNI and hold.

D-ATIS	ATLANTA APP CON	ATLANTA TOWER						ALL RWYS	GND CON	ALL RWYS
119.65	134.725 379.9	8L-26R	8R-26L	9L-27R	9R-27L	10-28	121.9	(8L-26R, 8R-26L) (9L-27R, 9R-27L) 10-28	121.75 121.65 254.4	254.4

RADAR REQUIRED

CATEGORY		A	B	C	D
LPV DA		1226/18		200 (200-½)	
LNAV/VNAV DA		1403/40		377 (500-¾)	
LNAV MDA		1480/24	454 (500-½)	1480/45	454 (500-⅞)

ATLANTA, GEORGIA

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

Amdb 4B 12OCT17

33°38'N-84°26'W

RNAV (GPS) RWY 9R