

WAAS CH 61000 W26B	APP CRS 275°	Rwy Ldg TDZE 990 Apt Elev 1026
--	------------------------	--

RNAV (GPS) Y RWY 26R

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Simultaneous approach authorized with Rwy 27R or 27L or 28, or Rwys 27R and 28. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 1500 then climbing right turn to 3500 direct TROYS and hold.

D-ATIS 119.65	ATLANTA APP CON 134.725 379.9	ATLANTA TOWER 8L-26R 8R-26L 9L-27R 9R-27L 10-28 RWYS 119.1 125.325 123.85 119.3 119.5 254.4						ALL RWYS 121.9	GND CON (8L-26R,8R-26L) (9L-27R,9R-27L) 10-28 121.75 121.65 254.4	ALL RWYS
-------------------------	--	--	--	--	--	--	--	-----------------------------	--	-------------

4 NM

TROYS

MSA RW26R 2.5 NM

1151

▲

RW26R

1148

(FAF)

AJAAY

2700

275°

(5)

BAMBU

4000

275°

(3.8)

(IF)

HAINZ

5000

275°

(6)

(IAF)

ZELOW

ELEV 1026

D

TDZE 990

275°

HIRL all Rwys

TDZL/RCLS Rwys 8L, 9R, 10, 26R, 27L and 28

RADAR REQUIRED				
1500 3500 TROYS △ VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 69°) HAINZ ZELOW				
*LNAV only. 1.3 3.9 NM 5 NM 3.8 NM 6 NM 1.3 3.9 NM 5 NM 3.8 NM 6 NM				
CATEGORY	A	B	C	D
LPV	DA	1190/18	200 (200-½)	
LNAV/VNAV	DA	1426/50	436 (500-1)	
LNAV MDA	1460/24	470 (500-½)	1460/50	470 (500-1)

ATLANTA, GEORGIA
Amdt 4A 12OCT17

HARTSFIELD/JACKSON ATLANTA INTL (ATL)

33°38'N-84°26'W

RNAV (GPS) Y RWY 26R

SE-4, 06 AUG 2026 to 03 SEP 2026

SE-4, 06 AUG 2026 to 03 SEP 2026