


APP CRS	Rwy Ldg	5801
079°	TDZE	727
	Apt Elev	778

RNAV (RNP) Y RWY 8

BOB HOPE (BUR)

RNP AR APCH.	MALSR	MISSED APPROACH: Climb to 1200 then climbing right turn to 4600 direct COTSI and on track 263° to YOLYY and hold. *Missed approach requires minimum climb of 340 feet per NM to 2400. # Missed approach requires minimum climb of 317 feet per NM to 2400.
For uncompensated Baro-VNAV systems, procedure NA below 1°C or above 54°C. Straight-in Rwy 8 at night, operational VGSi required, remain on or above VGSi glidepath until threshold. Inop table does not apply to RNP 0.20* and RNP 0.30. For inop ALS, increase RNP 0.30* all Cats visibility to 1 1/4 SM.		

D-ATIS	SOCAL APP CON	BURBANK TOWER	GND CON	CLNC DEL	CPDLC
134.5	120.4 360.6 (NORTH) 134.2 338.2 (WEST)	118.7 254.3	123.9 348.6	118.0 348.6	



YEBUN 3000 WESKI 2700 GP 3.00° TCH 60 079° 2700 1.2 NM 6 NM CATEGORY A B C D RNP 0.20 DA* 1068/50 341 (300-1) RNP 0.30 DA# 1151/50 424 (400-1) RNP 0.30 DA 1485-2½ 758 (800-2½) AUTHORIZATION REQUIRED				1200 4600 COTSI tr 263° YOLYY See planview for multiple IF locations. RW08	079° 5802 X 150 0.5% UP 26 33 15 8-26 15-33 33 15
--	--	--	--	---	--