

CHARLOTTE/DOUGLAS INTL (CLT)
CHARLOTTE, NORTH CAROLINA



KILNS SEVEN DEPARTURE (RNAV)

SE-2, 06 AUG 2026 to 03 SEP 2026


RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TAKEOFF MINIMUMS
Rwys 1R, 18L, 19L/R, 36R: Standard with minimum climb of 500' /NM to 1260.
Rwy 1L: Standard with minimum climb of 500' /NM to 1400.

CHARLOTTE DEP CON
124.0 307.8
D-ATIS DEP
132.1
CLINC DEL
127.15 348.6
CPDIC
GND CON
121.8 348.6 (W)
121.9 348.6 (E)
CHARLOTTE TOWER
1118.1 257.8 (18L-36R)
126.4 257.8 (1R-19L)
133.35 257.8 (1L-19R)



NOTE: Turbojet only.
NOTE: If unable to accept climb rates, advise ATC on initial contact.
NOTE: Transponder code will be issued via PDC or CLT CLNC DEL.
NOTE: Accelerate to 250K, if unable advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.



(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

KILNS SEVEN DEPARTURE (RNAV)

(KILNS7.KILNS) 09JUL26

CHARLOTTE, NORTH CAROLINA
CHARLOTTE/DOUGLAS INTL (CLT)



DEPARTURE ROUTE DESCRIPTION

SEE ADDITIONAL REQUIREMENTS ON AAUP

TAKEOFF RUNWAY 1L: Climb on heading 003° to 1260, then on heading 315° or as assigned by ATC for RADAR vectors to MUNBE, thence. . .

TAKEOFF RUNWAY 1R: Climb on heading 003° to 1260, then on heading 330° or as assigned by ATC for RADAR vectors to MUNBE, thence. . .

TAKEOFF RUNWAYS 18L, 19L: Climb on heading 183° to 1260, then on heading 183° or as assigned by ATC for RADAR vectors to MUNBE, thence. . .

TAKEOFF RUNWAY 19R: Climb on heading 183° to 1260, then on heading 200° or as assigned by ATC for RADAR vectors to MUNBE, thence. . .

TAKEOFF RUNWAY 36R: Climb on heading 003° to 1260, then on heading 025° or as assigned by ATC for RADAR vectors to MUNBE, thence. . .

. . . on depicted route to KILNS, then on AUDII Transition. Maintain 8000. Expect filed altitude 10 minutes after departure.

AUDII TRANSITION (KILNS7.AUDII)

SE-2, 06 AUG 2026 to 03 SEP 2026

SE-2, 06 AUG 2026 to 03 SEP 2026