

WAAS
CH **78306**
W07A

APP CRS
074°

Rwy Ldg
TDZE
Apt Elev

6052
13
14

RNAV (GPS) RWY 7

SANTA BARBARA MUNI (SBA)

RNP APCH - GPS.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 2°C or above 54°C. Circling Rwy 15L/R and 33L/R NA at night. Circling NA for Cats C and D north of Rwy 7-25. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cats C and D increase visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 700 then climbing right turn to 4000 direct GOLET and hold, continue climb-in-hold to 4000.

ATIS 132.65	SANTA BARBARA APP CON★ 120.55 319.15 (151°-329°) 125.4 291.1 (330°-150°)	SANTA BARBARA TOWER★ 119.7 (CTAF) 0 254.35	GND CON 121.7	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------

ELEV 14

D

TDZE 13

TWR

6052 X 150

7

074°

15R

15L

33L

33R

4184 X 100

4180 X 75

HIRL Rwy 7-25

MIRL Rwy 15R-33L

REIL Rwy 15R and 25

ECEVA	NAPPS	ADEEM	GOLET
2900	1800	1.9 NM to RW07	700 4000
074°	1800	1.3 NM to RW07	△
GP 3.00°			
TCH 52			
6.2 NM	3.5 NM	0.6	1.3 NM

CATEGORY	A	B	C	D
LPV DA	263/24 250 (300-½)			
LNAV/VNAV DA	480/50 467 (500-1)			
LNAV MDA	480/24	467 (500-½)	480/50 467 (500-1)	
CIRCLING	700-1 686 (700-1)	760-1 746 (800-1)	760-2¼ 746 (800-2¼)	900-3 886 (900-3)

SANTA BARBARA, CALIFORNIA

Amtd 2 19MAR26

34°26'N-119°50'W

SANTA BARBARA MUNI (SBA)

RNAV (GPS) RWY 7