


LOC/DME I-OGG	APP CRS	Rwy Ldg	6995
110.1	024°	TDZE	55
Chan 38		Apt Elev	55

ILS Z or LOC Z RWY 2
KAHULUI (OGG)(PHOG)

RNP APCH - GPS. From HOMAI or KEIKI or GREHG.
DME required.
For inop ALS, increase S-ILS 2 Cat E visibility to ¾ SM, and S-LOC 2 Cats C/D/E visibility to 1¾ SM.

MALS R	MISSED APPROACH: Climb to 3000 on OGG VORTAC R-023 to KRANE/OGG 13 DME and hold.
--------	--

ATIS 128.6	HCF APPROACH 120.2 322.4 (N) 119.5 225.4 (S)	MAUI TOWER ★ 118.7 (CTAF) 0 279.6	GND CON 121.9 279.6	UNICOM 122.95
---------------	--	--------------------------------------	------------------------	------------------



Use I-OGG DME when on the localizer course. VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 77).					
ZOXUP One Minute Holding Pattern 6700 ← 204° 4000 → 024° GS 3.00° TCH 62					
TEBBS I-OGG 8.5 RADAR 2400 1220					
NOWAK I-OGG 4.8 RADAR 2400 1220					
JUBEG I-OGG 2.5 I-OGG 1.3 2400 1220					
YEVLU I-OGG 1.3 2400 1220					
GREHG I-OGG 1.3 2400 1220					
CATEGORY	A	B	C	D	E
S-ILS 2	275-½ 220 (300-½)				
S-LOC 2	520-½	465 (500-½)	520-1	465 (500-1)	
CIRCLING	520-1 465 (500-1)	620-1 565 (600-1)	800-2¼ 745 (800-2¼)	1160-3 1105 (1200-3)	1720-3 1665 (1700-3)

