

WAAS CH 90509 W14A	APP CRS 144°	Rwy Ldg TDZE 1169 Apt Elev 1189
--	------------------------	---

RNAV (GPS) Y RWY 14L



GRANT COUNTY INTL (MWH)

RNP APCH.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.
▲ Baro-VNAV and VDP NA when using Ephrata altimeter setting. When local altimeter setting not received, use Ephrata altimeter setting; increase all DA 36 feet and all MDA 40 feet, increase LNAV/VNAV visibility all Cats ½ SM, LNAV Cats C and D and Circling Cat D ¼ SM.

MISSED APPROACH: Climb to 4000 direct HEDBI and on track 124° to UPBOB and hold.

ATIS 119.05	GRANT COUNTY APP CON ★ 126.4 379.95	GRANT COUNTY TOWER ★ 118.25 (CTAF) 0 257.8 (E) 128.0 257.8 (W)	GND CON 121.9	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).				
4 NM Holding Pattern	JUKRI	ILARE	4000 HEDBI	UPBOB
4000	324°	144°	3000	124°
GP 3.00° TCH 52		3000	VIMFY 1.8 NM to RW14L	
	6.4 NM	3.8 NM	0.7	1.1 NM
CATEGORY	A	B	C	D
LPV DA		1369-¾	200 (200-¾)	
LNAV/VNAV DA		1436-⅞	267 (300-⅞)	
LNAV MDA	1580-1	411 (400-1)	1580-1½	411 (400-1½)
CIRCLING	1660-1	471 (500-1)	1680-1½	1820-2
			491 (500-1½)	631 (700-2)