

IFR ALTERNATE AIRPORT MINIMUMS

Pilots must review the IFR Alternate Minimums Notes to determine alternate airport suitability.

NA designation on the approach chart means that pilots may not use that approach as an alternate due to unmonitored facility, absence of weather reporting service, or lack of adequate navigation coverage. Approaches with the NA designation are not listed in this section.  designation on the approach chart indicates that the approach procedure has non-standard minimums (for aircraft other than helicopters) or restrictions (for all users) for its use as an alternate. A procedure is not authorized for alternate flight planning purposes when local weather is not available.

MILITARY USERS NOTE: For IFR alternate airport and minima planning, refer to appropriate service directives.

Alternate Minima (ref: 14 CFR 91.169)

	Precision Approach	Non-Precision Approach
Standard	600-2	800-2
 Non-Standard or restrictions	As indicated below	As indicated below
Helicopters	For the selected approach: Ceiling: 200' above published ceiling Visibility: the greater of 1 SM visibility or the published visibility	

Note: For alternate airport flight planning purposes, precision approach operations include: ILS, PAR, and GLS, and Non-Precision approach operations include: NDB, VOR, LOC, TACAN, LDA, SDF, ASR, RNAV (GPS) and RNAV (RNP).

NAMEALTERNATE MINIMUMS

BABELTHUAP ISLAND, PW

PALAU INTL (ROR) (PTRO).....NDB Rwy 9¹
RNAV (GPS) Rwy 9
RNAV (GPS) Rwy 27

NA except standard for operators with approved weather reporting service.

¹Cat A, B 900-2, Cat C 900-2½, Cat D 900-2¼.

HANA, HI

HANA (HNM) (PHHN).....RNAV (GPS) Rwy 26
Cat A 900-2, Cat B 1100-2.

HILO, HI

HILO INTL (ITO) (PHTO).....ILS or LOC Rwy 26¹²
RNAV (GPS) Rwy 21³
RNAV (GPS) Rwy 26³
VOR-B³
VOR/DME or TACAN Rwy 26³
VOR/DME or TACAN-A³

¹NA when control tower closed.

²LOC Cat C 900-2¼, Cat D 1300-3.

³Cat C 900-2¼, Cat D 1300-3.

NAMEALTERNATE MINIMUMS

HONOLULU, HI

DANIEL K INOUE
INTL (HNL) (PHNL).....LOC Rwy 4R¹
LOC Rwy 8L²
RNAV (GPS) Rwy 4L³
RNAV (GPS) Rwy 8R⁴
RNAV (GPS) Y Rwy 4R⁵
RNAV (GPS) Y Rwy 8L²
VOR or TACAN Rwy 4R⁶
VOR or TACAN Rwy 8R⁷
VOR or TACAN-A⁴
VOR or TACAN-B¹

¹Cat C 800-2¼, Cat D 1400-3.

²Cat C 900-2¼, Cat D 1300-3.

³Cat C 900-2¼, Cat D 1400-3, Cat E 2000-3.

⁴Cat C 900-2¼, Cat D 1400-3, Cat E 2100-3.

⁵Cat C 900-2¼.

⁶Cat C 900-2¼, Cat D 1400-3.

⁷Cat C 900-2¼, Cat D 1300-3, Cat E 2000-3.

KAHULUI, HI

KAHULUI (OGG)
(PHOG).....ILS Y or LOC Y Rwy 2¹²
ILS Z or LOC Z Rwy 2¹²
RNAV (GPS) Rwy 20³
RNAV (GPS) Rwy 23⁴
RNAV (GPS) Y Rwy 2⁵⁶
VOR Z or TACAN Rwy 20³

¹NA when control tower closed.

²LOC Cat C 800-2¼, Cat D 1200-3, Cat E 1700-3.

³Cat D 1100-3.

⁴Cat D 1200-3.

⁵NA when local weather not available.

⁶Cat C 800-2¼, Cat D 1200-3.

NAME	ALTERNATE MINIMUMS
KAILUA-KONA, HI	
ELLISON ONIZUKA KONA INTL AT	
KEAHOLE (KOA) (PHKO).....	ILS or LOC Rwy 17¹
	RNAV (GPS) Rwy 35
	RNAV (GPS) Y Rwy 17
	VOR or TACAN Rwy 17
	VOR or TACAN Rwy 35
NA when local weather not available.	
¹ NA when control tower closed.	

KAPOLEI, HI

KALAELOA (JOHN RODGERS
FLD) (JRF) (PHJR).....**NDB Rwy 4R¹**
RNAV (GPS) Rwy 4R
VOR Rwy 4R

NA when local weather not available.
¹Cat A, B, C, D 800-2³/₄.

KAUNAKAKAI, HI

¹NA when local weather not available.
²Cat C 1200-3, Cat D 1500-3.
³Cat A, B 1500-2, Cat C, D 1500-3.

KOSRAE, FM

¹NA except standard for operators with approved weather reporting service.

²NA except Cat A, B standard, Cat C 800-2¼, Cat D 800-2½, for operators with approved weather reporting service.

LANAI CITY, HI

LANAI (LNY) (PHNY).....RNAV (GPS) Rwy 3¹
VOR or TACAN or GPS-A²

¹Cat C 1000-2%.

²NA when local weather not received except for operators with approved weather reporting service.

LIHUE, HI

LIHUE (LIH) (PHLI).....ILS or LOC Rwy 35¹
 RNAV (GPS) Rwy 17²³
 RNAV (GPS) Y Rwy 21²³
 RNAV (GPS) Y Rwy 35⁴
 RNAV (RNP) Z Rwy 21⁵
 VOR or TACAN Rwy 21²

¹NA when control tower closed.
²NA when local weather not available.
³Cat C, D 800-2½.
⁴Cat C 800-2¼, Cat D 800-2½.
⁵RNP 0.30. Cat A. B. C. D 1000-4.

NAME	ALTERNATE MINIMUMS
MIDWAY ATOLL, QM	
HENDERSON	
FLD (MDY).....	NDB Rwy 6
	NDB Rwy 24
	RNAV (GPS) Rwy 6
	RNAV (GPS) Rwy 24
NA except standard for operators with approved weather reporting service.	

PAGO PAGO, AS

PAGO PAGO
INTL (PPG) (NSTU).....ILS or LOC Rwy 5¹
RNAV (GPS) Rwy 5²
RNAV (GPS) Rwy 23²
VOR or TACAN-B²

¹ILS Cat A, B, C, D 900-2; LOC Cat C 800-2½,
Cat D 900-2¾.
²Cat C 800-2¼, Cat D 900-2¾.

POHNPEI ISLAND. FM

POHNPEI INTL (PNI) (PTPN).....NDB-A¹
RNAV (GPS) Rwy 27²
RNAV (GPS) X Rwy 9¹

ROTA ISLAND. MP

BENJAMIN TAISACAN MANGLONA
INTL (GRO) (PGRO).....RNAV (GPS) Rwy 9
RNAV (GPS) Rwy 27
NDB Rwy 9¹
NDB Rwy 27
NA except standard for operators with approved
weather reporting service.
¹ Cat A, B 1200-2. Cat C, D 1200-3.

SAIPAN ISLAND. MP

SAIPAN INTL (GPN) (PGSN).....NDB Y Rwy 7
Cat D 800-2¼.

TAMUNING, GU

INTL (GUM) (PGUM).....ILS or LOC Rwy 6L¹
 ILS or LOC Rwy 6R¹
 RNAV (GPS) Y Rwy 24L²
 RNAV (GPS) Y Rwy 24R³
 VOR or TACAN Rwy 24R³

¹LOC Cat A, B 1200-2, Cat C, D 1200-3.
²Cat A, B 900-2, Cat C 900-2½, Cat D 900-3.
³Cat A, B 900-2, Cat C, D 900-2½.

TINIAN ISLAND, MP

FRANCISCO MANGLONA BORJA
TINIAN INTL (TNI) (PGWT).....RNAV (GPS) Rwy 8
RNAV (GPS) Rwy 26
NA when local weather not available.
Cat D 800-2%.

NAME

ALTERNATE MINIMUMS

NAME

ALTERNATE MINIMUMS

WENO ISLAND, FM

CHUUK INTL (TKK) (PTKK).....**NDB Rwy 4¹**
NDB Rwy 22²³
RNAV (GPS) Rwy 4²⁴
RNAV (GPS) Rwy 22²⁵

¹NA except for operators with approved weather reporting service. Cat A, B, C, D 800-2½.
²NA except standard for operators with approved weather reporting service.
³Cat C, D 800-2½.
⁴Cat A, B, C, D 800-3.
⁵Cat A, B 900-2, Cat C 900-2½, Cat D 900-2¾.

YAP ISLAND, FM

YAP INTL (T11) (PTYA).....**NDB Rwy 7¹**
NDB Rwy 25²
NDB/DME Rwy 25²

¹Cat D 800-2½.
²Cat A, B 1000-2, Cat C, D 1000-3.

09 JUL 2026 to 03 SEP 2026

09 JUL 2026 to 03 SEP 2026