




SE-2, 03 SEP 2026 to 01 OCT 2026

TOP ALTITUDE:
8000

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

- CHARLOTTE DEP CON
120.5 257.2
D-ATIS DEP
132.1
CLINC DEL
127.15 348.6
CPDLC
GND CON
121.8 348.6 (W)
121.9 348.6 (E)
CHARLOTTE TOWER
118.1 257.8 (18-36)
126.4 257.8 (1R-19L)
133.35 257.8 (1L-19R)

TAKEOFF MINIMUMS
Rwys 1R, 18, 19L/R, 36: Standard with minimum climb of 500' /NM to 1260.
Rwy 1L: Standard with minimum climb of 500' /NM to 1400.



- NOTE: Turbojet only.
- NOTE: If unable to accept climb rates, advise ATC on initial contact.
- NOTE: Transponder code will be issued via PDC or CLT CLINC DEL
- NOTE: Accelerate to 250K, if unable advise ATC. Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-2, 03 SEP 2026 to 01 OCT 2026



DEPARTURE ROUTE DESCRIPTION

SEE ADDITIONAL REQUIREMENTS ON AAUP

TAKEOFF RUNWAY 1L: Climb on heading 003° to 1260, then on heading 315° for vectors to GINNN, thence. . .

TAKEOFF RUNWAY 1R: Climb on heading 003° to 1260, then on heading 330° for vectors to GINNN, thence. . .

TAKEOFF RUNWAYS 18, 19L: Climb on heading 183° to 1260, for vectors to GINNN, thence. . .

TAKEOFF RUNWAY 19R: Climb on heading 183° to 1260, then on heading 200° for vectors to GINNN, thence. . .

TAKEOFF RUNWAY 36: Climb on heading 003° to 1260, then on heading 025° for vectors to GINNN, thence. . .

. . .on track 255° to ESTRR, then on IPTAY Transition. Maintain 8000. Expect filed altitude 10 minutes after departure.

IPTAY TRANSITION (ESTRR8.IPTAY)