

WAAS CH 56205 W28B	APP CRS 283°	Rwy Ldg 11000 TDZE 23 Apt Elev 31
--	------------------------	--


RNAV (GPS) X RWY 28L
PORTLAND INTL (PDX)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 54°C (130°F). Simultaneous approach authorized.
LNAV procedure NA during simultaneous operations. DME/DME RNP-0.3 NA.
Use of FD or AP providing RNAV track guidance required during simultaneous operations. For inop ALS, increase LNAV Cat C/D visibility to 1½ SM.

MALS R

MISSED APPROACH: Climb to 2100 then climbing left turn to 4000 direct UBG VOR/DME and hold.

D-ATIS 128.35 269.9	PORTLAND APP CON 124.35 299.2	PORTLAND TOWER 118.7 257.8 (10L-28R) 123.775 251.125 (3-21, 10R-28L)	GND CON 121.9 348.6
-------------------------------	---	--	-------------------------------



ELEV 31 **D** TDZE 23

MAVER

Procedure NA for arrivals at MAVER on V448 southbound and on V165 eastbound.

2100 4000 UBG

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

HANAH HPSTR

YINUP ADDUM

3.8 NM to RWY 28L

2000 283° 3700

1280* 2000

GP 3.00° TCH 55

1.4 2.4 NM 2.2 NM 3 NM 4.4 NM

CATEGORY	A	B	C	D
LPV DA	309/22 286 (300-½)			
LNAV/VNAV DA	368/30 345 (400-⅝)			
LNAV MDA	540/24 517 (600-½)		540/55 517 (600-1)	
CIRCLING	720-1 689 (700-1)	760-1 729 (800-1)	1060-3 1029 (1100-3)	

NW-1, 03 SEP 2026 to 01 OCT 2026

NW-1, 03 SEP 2026 to 01 OCT 2026