

GREER, SOUTH CAROLINA

AL-5124 (FAA)

26190

LOC/DME I-GSP	APP CRS	Rwy Ldg
109.3	038°	11001
Chan 30		TDZE 947
		Apt Elev 964

ILS or LOC RWY 4

GREENVILLE SPARTANBURG INTL (GSP)


DME required.

For inop ALS, increase S-LOC 4 Cats C and D visibility to RVR 5500. When local altimeter setting not received, use Greenville Downtown altimeter setting: increase DA to 1176 feet; increase all MDAs 40 feet and visibility S-LOC 4 Cat C/D to RVR 4000 and Circling Cat D ¼ SM. For inop ALS, when using Greenville Downtown altimeter setting, increase S-LOC 4 Cats C/D visibility to RVR 6000.

ALSIF-2

MISSED APPROACH: Climb to 3000 then right turn direct SPA VORTAC and hold.

ATIS 134.25	GREER APP CON★ 118.8 270.275	GREER TOWER★ 120.1(CTAF) 251.15	GND CON 121.9	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------



One Minute Holding Pattern

5400 ← 218°
3000 → 038°

GS 3.00°
TCH 55

OXABY I-GSP 12.9

MULDE I-GSP 6

JOKVA I-GSP 3.4

I-GSP 1.9

*LOC only.

3000

SPA

2300

*1460

6.9 NM

2.6 NM

1.5 NM

CATEGORY	A	B	C	D
S-ILS 4	1147/18 200 (200-½)			
S-LOC 4	1320/24	373 (400-½)	1320/35	373 (400-¾)
CIRCLING	1440-1	476 (500-1)	1480-1½ 516 (600-1½)	1700-2¼ 736 (800-2¼)

ELEV 964

TDZE 947

RCLS Rwy 22

HIRL Rwy 4-22

TDZL/RCLS Rwy 4

GREER, SOUTH CAROLINA
Amdt 25 05DEC19

34°54'N-82°13'W

GREENVILLE SPARTANBURG INTL (GSP)

ILS or LOC RWY 4

SE-2, 06 AUG 2026 to 03 SEP 2026

SE-2, 06 AUG 2026 to 03 SEP 2026

GREER, SOUTH CAROLINA

AL-5124 (FAA)

26246

LOC/DME I-GSP	APP CRS	Rwy Ldg
109.3	038°	11001
Chan 30		TDZE 947
		Apt Elev 964

ILS or LOC RWY 4

GREENVILLE SPARTANBURG INTL (GSP)


DME required.

For inop ALS, increase S-LOC 4 Cats C and D visibility to RVR 5500. When local altimeter setting not received, use Greenville Downtown altimeter setting: increase DA to 1176 feet; increase all MDAs 40 feet and visibility S-LOC 4 Cat C/D to RVR 4000 and Circling Cat D ¼ SM. For inop ALS, when using Greenville Downtown altimeter setting, increase S-LOC 4 Cats C/D visibility to RVR 6000.

ALS-F-2

MISSED APPROACH: Climb to 3000 then right turn direct SPA VORTAC and hold.

ATIS 134.25	GREER APP CON★ 118.8 270.275	GREER TOWER★ 120.1(CTAF) 251.15	GND CON 121.9	UNICOM 122.95
-----------------------	--	---	-------------------------	-------------------------



One Minute Holding Pattern		OXABY I-GSP 12.9	MULDE I-GSP 6	JOKVA I-GSP 3.4	SPA I-GSP 1.9
5400 ← 218°		3000 → 038°	2300	2300	2300
GS 3.00° TCH 55		6.9 NM	2.6 NM	1.5 NM	
CATEGORY	A	B	C	D	
S-ILS 4	1147/18 200 (200-½)				
S-LOC 4	1320/24	373 (400-½)	1320/35	373 (400-¾)	
CIRCLING	1440-1	476 (500-1)	1480-1½ 516 (600-1½)	1700-2¼ 736 (800-2¼)	

ELEV 964 TDZE 947

RCLS Rwy 22
HIRL Rwy 4-22
TDZL/RCLS Rwy 4

GREER, SOUTH CAROLINA
Amdt 25 05DEC19

34°54'N-82°13'W

ILS or LOC RWY 4