



LOC/DME I-SBA	APP CRS	Rwy Ldg	6052
110.3	075°	TDZE	13
Chan 40		Apt Elev	14

ILS or LOC RWY 7
SANTA BARBARA MUNI (SBA)


⚠ VDP NA when using OXR altimeter setting. Circling Rwy 15L/R and 33L/R NA at night. When local altimeter setting not received, use OXR altimeter setting: increase DA to 296 feet; increase all MDAs 100 feet and S-LOC 7 visibility Cats C and D to 1½ SM, Circling Cat A visibility to 1¼ SM and Circling visibility Cat C to 2¾ SM. For inop ALS, when using OXR altimeter setting, increase S-ILS 7 all Cats visibility to RVR 4500 and S-LOC 7 Cats C and D visibility to 1¾ SM. Circling NA for Cats C and D north of Rwy 7-25.
* RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using OXR altimeter setting).

MISSED APPROACH:
Climb to 700 then climbing right turn to 4000 on RZS VORTAC R-185 to GOLET INT/RZS 14.4 DME and hold, continue climb-in-hold to 4000.

ATIS 132.65	SANTA BARBARA APP CON★ 120.55 319.15 (151°-329°) 125.4 291.1 (330°-150°)	SANTA BARBARA TOWER★ 119.7 (CTAF) 0 254.35	GND CON 121.7	UNICOM 122.95
----------------	--	---	------------------	------------------



	HABUT I-SBA [12.8]	GOYED INT I-SBA [9.5]	NAPPS INT I-SBA [6.7]	GOLET RZS [14.4]
	3500	2600	1800	1200
GS 3.00° TCH 52				
	3.4 NM	2.8 NM	3.9 NM	1.6 NM
CATEGORY	A	B	C	D
S-ILS 7*	213/24 200 (200-½)			
S-LOC 7	560/24	547 (600-½)	560/60	547 (600-1¼)
CIRCLING	800-1 786 (800-1)	840-1¼ 826 (900-1¼)	840-2½ 826 (900-2½)	1000-3 986 (1000-3)



SW-3, 01 OCT 2026 to 29 OCT 2026

SW-3, 01 OCT 2026 to 29 OCT 2026