

ILS or LOC RWY 15

LOC I-GRF
108.3
Chan **20**

APCH CRS
151°

Rwy Idg **6124**
TDZE **300**
Arprt Elev **301**

[USA] GRAY AAF (JOINT BASE LEWIS MCCHORD) (KGRF)

RNAV1-GPS from SEA VORTAC

DME required for civil use. For non-RNAV aircraft, RADAR required from SEA VORTAC.

* When ALS inop when using McChord AFB altimeter setting, increase LOC CAT C/D vis to RVR 55.

ATIS
124.65 306.2

SEATTLE APP CON
120.1 290.9

TOWER★
119.325 (CTAF) 256.8

GND CON
121.9 290.2

** Circling not authorized W of Rwy 15-33.

When local altimeter setting not received, use McChord AFB altimeter setting.
Procedure NA for arrival on OLM VORTAC airway radials 346 CW 012 and arrival on SEA VORTAC airway radials 168 CW 230

Procedure NA for arrival at OLM VORTAC for TACAN-only equipped aircraft.

OLYMPIA
113.4 OLM
Chan 81

SEA VORTAC
116.8 SEA
Chan 115

LOCALIZER 108.3
I-GRF
Chan 20

RAINIER 1 MOA
RAINIER 2 MOA

CATEGORY	A	B	C	D
S-ILS 15	500/24		200 (200-½)	
S-LOC 15	640/24	340 (400-½)	640/26	340 (400-½)
CIRCLING**	840-1	539 (600-1)	840-1½ 539 (600-1½)	920-2 619 (700-2)
McCHORD FLD ALTIMETER SETTING MINIMUMS				
S-ILS 15	516/24		216 (300-½)	
S-LOC 15*	660/24	360 (400-½)	660/35	360 (400-¾)
CIRCLING**	860-1	559 (600-1)	860-1½ 559 (600-1½)	940-2 639 (700-2)

ELEV 301 TDZE 300

HIRL Rwy 15-33

FAF to MAP 4.0 NM

Knots	60	90	120	150	180
Min:Sec	4:00	2:40	2:00	1:36	1:21

NW-1, 01 OCT 2026 to 29 OCT 2026

NW-1, 01 OCT 2026 to 29 OCT 2026