

LOC/DME I-ONT 109.7 Chan 34	APP CRS 258°	Rwy Ldg TDZE 12197 Apt Elev 932	26R 10200 926	26L 944 944
---	------------------------	---	-----------------------------------	---------------------------------

ILS or LOC RWY 26R
ONTARIO INTL (ONT)


RNP APCH - GPS. From TAKOE.
Circling NA north of Rwy 8L-26R. For inop ALS, increase S-LOC 26R Cat C and D visibility to 2 SM.

ALSF-2 Rwy 26R


ALSF-2 Rwy 26L

MISSED APPROACH: Climb to 2800 then climbing left turn to 5400 direct PDZ VORTAC and hold, continue climb-in-hold to 5400.
--

D-ATIS 124.25	SOCAL APP CON 127.0 318.2	ONTARIO TOWER 120.6 360.775	GND CON 121.9 257.8
-------------------------	-------------------------------------	---------------------------------------	-------------------------------



ELEV 944	D	TDZE 26R 932 TDZE 26L 926
-----------------	----------	--



CATEGORY	A	B	C	D
S-ILS 26R	1132/18 200 (200-½)			
S-LOC 26R	1680/24 748 (800-½)	1680/40 748 (800-¾)	1680-1¾ 754 (800-1¾)	748 (800-1¾)
SIDESTEP 26L	1680/55	754 (800-1)	1680-1¾ 754 (800-1¾)	1680-2 754 (800-2)
CIRCLING	1680-1 736 (800-1)	1680-1¼ 736 (800-1¼)	1680-2¼ 736 (800-2¼)	1680-2½ 736 (800-2½)
WUNAK FIX MINIMUMS (DME REQUIRED)				
S-LOC 26R	1320/24	388 (400-½)	1320/35	388 (400-¾)