ATLANTA, GEORGIA

AL-26 (FAA)

RNAV (GPS) PRM Y RWY 10
(SIMULTANEOUS CLOSE PARALLEL)
HARTSFIELD/JACKSON ATLANTA INTL (ATL)

WAAS CH 40399 W10A	APP CRS 095°	Rwy Ldg 9000 TDZE 1000 Apt Elev 1026

T NA For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C (20°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. For inop ALSF-2, increase LNAV/VNAV all Cats visibility to 1½ mile. Simultaneous close parallel approach authorized with ILS PRM and RNAV PRM Rwy 8L or 8R or 9L or 9R, or Rwys 8L and 9L, or Rwys 8L and 9R, or Rwys 8R and 9L, or Rwys 8R and 9R. See additional requirements on AAUP. Dual VHF comm required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.


ALSF-2

MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 direct SCARR and hold.


D-ATIS	ATLANTA APP CON	ATLANTA TOWER					
		8L-26R	8R-26L	9L-27R	9R-27L	10-28	ALL RWYS
119.65	134.725 379.9	119.1	125.325	123.85	119.3	119.5	254.4
		PRM 132.55					

GND CON			
(8L-26R,8R-26L)	(9L-27R,9R-27L)	10-28	ALL RWYS
121.9	121.75	121.65	254.4

RADAR REQUIRED




MISSED APCH FIX
SCARR
005°
185°
4 NM



CATEGORY	A	B	C	D
LPV DA	1200/18		200 (200-½)	
LNAV/VNAV DA	1455/55		455 (500-1)	

ELEV 1026 D TDZE 1000



HIRL all Rwys
TDZL/RCLS Rwys 8L, 9R, 10, 26R, 27L and 28

ATLANTA, GEORGIA
Orig-A 12OCT17

33°38'N-84°26'W HARTSFIELD/JACKSON ATLANTA INTL (ATL)

RNAV (GPS) PRM Y RWY 10 (SIMULTANEOUS CLOSE PARALLEL)

SE-4, 29 OCT 2026 to 26 NOV 2026