

WAAS CH 45626 W26A	APP CRS 246°	Rwy Idg TDZE Apt Elev	6543 396 400
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 26


BLYTHE (BLH)


⚠

When local altimeter setting not received, procedure NA.
DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.
#Missed approach requires a minimum climb of 375 feet per NM to 3500.
*Missed approach requires a minimum climb of 345 feet per NM to 3500.

MISSED APPROACH: Climbing right turn to 5400 direct ROGBE and hold, continue climb-in-hold to 5400.

ASOS 120.175	LOS ANGELES CENTER 128.15 285.6	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



5400	ROGBE	WUVER		
				
				
CATEGORY	A	B	C	D
*LP MDA	800-1	404 (400-1)	800-1½	404 (400-1½)
LP MDA	1940-1¼ 1544 (1600-1¼)	1940-1½ 1544 (1600-1½)	1940-3	1544 (1600-3)
# LNAV MDA	800-1	404 (400-1)	800-1½	404 (400-1½)
LNAV MDA	2060-1¼ 1664 (1700-1¼)	2060-1½ 1664 (1700-1½)	2060-3	1664 (1700-3)
CIRCLING	2060-1¼ 1660 (1700-1¼)	2060-1½ 1660 (1700-1½)	2060-3	1660 (1700-3)

