AIRPORT DIAGRAM

26134

HIRL Rwys 1L-19R, 8L-26R and 8R-26L
MIRL Rwy 1R-19L
REIL Rwys 19R, 1R, 19L and 8R

115°10'W 115°09'W 115°08'W 36°06'N 36°05'N

FBO
ELEV 2082
ELEV 2078
VAR 11° E
JANUARY 2020
ANNUAL RATE OF CHANGE
0.1° W
FUEL TANK FARM
FUEL TANK FARM
WEST CHARTER RAMP
9770 X 150
9769 X 150
1.1% DOWN
0.9% UP
194°
014°
079°
259°
HOLDING PAD
NORTHEAST HOLDING PAD
N & S HOLDING PADS
"A" GATE
"B" GATE
"C" GATE
"D" GATE
FIRE STATION
HOLDING PADS
PARADISE HOLDING PAD
TWR
TERMINAL 3 (E Gates)
HOLDING PAD
RON
AIR CARGO
FBO
LAHSO
SEE INSET
ELEV 2181
FIELD ELEV 2183
HS 1
ELEV 2175
ELEV 2157
14835 X 150
10526 X 150
1.2% DOWN
ELEV 2033
ELEV 2048

Departure runway misalignment risk.
RWY 8L AND RWY 1L HOLD LINE
LAHSO
RWY 1L HOLD LINE

D-ATIS
132.4
LAS VEGAS TOWER
118.75 (RWYS 01L-19R, 01R-19L)
119.9 (RWYS 08L-26R, 08R-26L)
257.8
GND CON
121.1 270.8 (E OF 01R-19L)
121.9 254.3 (W OF 01L-19R)
CLNC DEL
118.0
CPDLC
PDC
D

RWY 01L-19R
PCR 1090 R/B/W/T
S-120, D-250, 2D-550, 2D/2D2-1120
RWY 01R-19L
PCR 1230 R/B/W/T
S-120, D-250, 2D-550, 2D/2D2-1120
RWY 08L-26R
PCR 1130 R/C/W/T
S-120, D-250, 2D-550, 2D/2D2-1120
RWY 08R-26L
PCR 1150 R/B/W/T
S-120, D-250, 2D-550, 2D/2D2-1120

Ramp Frequencies ★:
124.4 A, B, C GATES & GA, CUSTOMS
127.9 D, E GATES & CARGO
130.0 RAMP ALTERNATE FREQUENCY

ASDE-X in use. Operate transponders with altitude reporting mode and ADS-b (if equipped) enabled on all airport surfaces.
Runway Status Lights in operation.

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

AL-662 (FAA)

LAS VEGAS, NEVADA
HARRY REID INTL (LAS)