
HONOLULU TWO DEPARTURE (OBSTACLE)



TAKEOFF MINIMUMS

Rwys 4W, 8W, 22W, 26W: NA-ATC.
Rwys 22L/R, 26R: Standard.
Rwys 4L/R: Standard with minimum climb of 425' per NM to 1900, do not exceed 180K until southeast bound on 155° heading, or 1700-2½ for VCOA.
Rwy 8L: Standard with minimum climb of 310' per NM to 1000, or 1700-2½ for VCOA.
Rwy 8R: Standard with minimum climb of 270' per NM to 1000, or 1700-2½ for VCOA.
Rwy 26L: Standard with minimum climb of 237' per NM to 300, or 1700-2½ for VCOA.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 4L/R, 8L/R: Climbing right turn to 3000 on heading 155° to intercept HNL R-125 to HAUNA INT before proceeding on course, or. . . .

TAKEOFF RUNWAYS 22L/R, 26L/R: Climbing left turn to 3000 on heading 140° to intercept HNL R-171 to ALANA INT before proceeding on course, or. . . .

. . . .for visual climb over airport: obtain ATC approval for VCOA when requesting IFR clearance. Climb in visual conditions to cross Daniel K. Inouye Intl Airport southbound at 1600, continue climb to 3000 on HNL R-171 to ALANA INT before proceeding on course.

PAC, 29 OCT 2026 to 24 DEC 2026
PAC, 29 OCT 2026 to 24 DEC 2026

TAKEOFF OBSTACLE NOTES

Rwy 4L: Multiple lights beginning 630′ from DER, 236′ left of centerline, 102′ right of centerline, up to 84′ AGL/92′ MSL.
Light on building 669′ from DER, 394′ left of centerline, 29′ AGL/37′ MSL.
Stack on building 2488′ from DER, 219′ right of centerline, 72′ AGL/80′ MSL.
Multiple trees beginning 1253′ from DER, 209′ left of centerline, 935′ right of centerline, up to 64′ AGL/72′ MSL.
Bush 450′ from DER, 234′ left of centerline, 14′ AGL/22′ MSL.

Rwy 4R: Stack on building, 2442′ from DER, 283′ left of centerline, 72′ AGL/80′ MSL.
Multiple trees beginning 1206′ from DER, 711′ left of centerline, 433′ right of centerline, up to 64′ AGL/72′ MSL.
Multiple lights beginning 1072′ from DER, 399′ left of centerline, 504′ right of centerline, up to 36′ AGL/44′ MSL.
Pole 2110′ from DER, 951′ left of centerline, 59′ AGL/67′ MSL.

Rwy 22L: Multiple bushes beginning 265′ from DER, 396′ right of centerline, up to 17′ AGL/31′ MSL.
Tree 1065′ from DER, 499′ right of centerline, 30′ AGL/38′ MSL.

Rwy 22R: Rod on obstruction light ASR 1451′ from DER, 827′ right of centerline, 76′ AGL/84′ MSL.
Tree 853′ from DER, 308′ right of centerline, 43′ AGL/51′ MSL.

Rwy 26L: Ship 1.1 NM from DER, on centerline, 208′ AGL/208′ MSL.

Rwy 26R: Multiple light poles beginning 2120′ from DER, 813′ right of centerline, up to 105′ AGL/111′ MSL.

PAC, 29 OCT 2026 to 24 DEC 2026
PAC, 29 OCT 2026 to 24 DEC 2026