

ILS or LOC RWY 3

LOC/DME I-NTD 109.3 Chgn 30	APCH CRS 032°	Rwy Idg 11,102 TDZE 10 Arpt Elev 13
---	-------------------------	--

[USN]

POINT MUGU NAS (NAVAL BASE VENTURA CO) (KNTD)

DME or RADAR required.


T * When ALS inop, increase vis to 1 mile.
 ** Circling not authorized SE of Rwy 3-21.
 CAT A remain within 1.3 NM, CAT B remain within 1.5 NM,
 CAT C remain within 1.7 NM, CAT D remain within 2.3 NM.

SALSF

MISSED APPROACH: Climb to 500, then climbing left turn to 2600 on heading 181° and NTD TACAN R-211 to HALTU and hold.

ATIS ★	APP CON	TOWER ★	GND CON	ASR/ PAR
125.55 363.05	128.65 307.275	124.85 290.375	121.6 360.2	

ILS glideslope not useable beyond 8 NM.



EMERG SAFE ALT 100 NM 12,300

OXNARD, CALIFORNIA

34° 07' N - 119° 07' W

POINT MUGU NAS (NAVAL BASE VENTURA CO) KNTD

Orig 27NOV25

PANS-OPS

ILS or LOC RWY 3