

WAAS CH 70624 W26A	APP CRS 259°	Rwy Ldg TDZE 1005 Apt Elev 1014
--	------------------------	---

RNAV (GPS) RWY 26L

BRACKETT FLD (POC)

RNP APCH.

⚠

Baro-VNAV and VDP NA when using Ontario altimeter setting. Rwy 26L helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Ontario Intl altimeter setting and increase all DA 32 feet and all MDA 40 feet, increase LPV and LNAV/VNAV all Cats visibility ⅓ SM. Circling NA for Cat C north of Rwy 8L-26R. Circling to Rwy 8L NA at night. When Circling to Rwy 8R at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MISSED APPROACH:

Climb to 2100 then climbing left turn to 4000 direct PRADO and hold.

ATIS 124.4	SOCAL APP CON 125.5 349.0	BRACKETT TOWER★ 118.2 (CTAF) (8R/26L) 133.3 (8L/26R)	GND CON 125.0	UNICOM 122.95
----------------------	-------------------------------------	--	-------------------------	-------------------------

ELEV 1014	TDZE 1005
-----------	-----------

2100		4000	PRADO	VGSI and RNAV glidepath not coincident (VGSI Angle 3.76/TCH 18).	
↑		↙	△	LIZZE 4 NM Holding Pattern	
*LNAV only		ZERЕК 2.1 NM to RW26L	WUDUS 3200	LIZZE 4 NM Holding Pattern	
RW26L		*1.2 NM to RW26L	3200	GP 3.56° TCH 58	
1.2 NM		0.9 NM	3.6 NM	7.2 NM	
CATEGORY		A	B	C	D
LPV DA		1305-7/8 300 (300-7/8)			NA
LNAV/VNAV DA		1444-1¼ 439 (500-1¼)			NA
LNAV MDA		1500-1	495 (500-1)	1500-1¾ 495 (500-1¾)	NA
CIRCLING		1680-1	666 (700-1)	1760-2¼ 746 (800-2¼)	NA

LA VERNE, CALIFORNIA

Amtd 1 03JAN19

BRACKETT FLD (POC)

34°06'N-117°47'W

RNAV (GPS) RWY 26L