

LOC/DME I-CRQ 108.7 Chan 24	APP CRS 245°	Rwy Ldg TDZE Apt Elev 4897 326 331	ILS or LOC RWY 24 MC CLELLAN-PALOMAR (CRQ)
---	------------------------	--	---

▼


▲

Inop table does not apply to S-ILS Rwy 24.
Autopilot coupled approach NA below 960. DME required.
Rwy 24 helicopter visibility reduction below RVR 4000 NA. For inop ALS, increase S-LOC 24 Cat A/B visibility to RVR 5500 and Cat C visibility to 1% SM.


MALSR

MISSED APPROACH: Climb to 3000 on heading 245° and on OCN VORTAC R-145 to OCN VORTAC and hold.

ATIS 120.15	SOCAL APP CON 127.3 323.0	PALOMAR TOWER★ 118.6 (CTAF) 0 276.4	GND CON 121.8
-----------------------	-------------------------------------	---	-------------------------



ELEV 331	D	TDZE 326
----------	---	----------



CATEGORY	A	B	C	D
S-ILS 24	527/40	201 (200-¾)	576/40 250 (300-¾)	NA
S-LOC 24	1000/40	674 (700-¾)	1000-1½ 674 (700-1½)	NA
CIRCLING	1000-1 669 (700-1)	1020-1 689 (700-1)	1260-2¾ 929 (1000-2¾)	NA