RUKKI ONE ARRIVAL (RNAV)

(RUKKI.RUKKI1) 26DEC24

SANTA ANA, CALIFORNIA

JOHN WAYNE/ORANGE COUNTY (SNA)

(RUKKI.RUKKI1) 24361

AL-377 (FAA)

RUKKI ONE ARRIVAL (RNAV)

JOHN WAYNE/ORANGE COUNTY (SNA)

SANTA ANA, CALIFORNIA

SOCAL APP CON
127.4 263.025
D-ATIS
126.0
JOHN WAYNE TOWER★
126.8 343.625

ARRIVAL ROUTE DESCRIPTION

TCUPS TRANSITION (TCUPS.RUKKI1)

TILLT TRANSITION (TILLT.RUKKI1)

From RUKKI on track 108° to SCANN, then on track 109° to cross BAUBB between 11000 and 13000.

LANDING RUNWAY 2L: From BAUBB on track 099° to cross JJAWS at or below 6000, then on track 092° to cross PUZZL at 5000 and at 220K, then on track 017° to cross MINOE at 3000 and at 210K. Expect RNAV (RNP) Z RWY 2L approach or RADAR vectors to final approach course.

LANDING RUNWAY 20R: From BAUBB on track 089° to cross STYFF at or below 9000, then on track 080° to cross KAYNN at or below 7000, then on track 057° to cross LAXBB at 5000 and at 200K, then on track 044° to cross KLEVR at 5000 and at 200K, then on track 016°. Expect RNAV (RNP) Z RWY 20R approach or RADAR vectors to final approach course.

LOST COMMUNICATIONS

LANDING RUNWAY 20R: After KLEVR execute RNAV (RNP) Z RWY 20R approach, or proceed to SAGER and execute the ILS or LOC RWY 20R approach.

LANDING RUNWAY 2L: Proceed on LOC BC RWY 2L, RNAV (GPS) Y RWY 2L, or RNAV (RNP) Z RWY 2L approach.

RNAV 1 - DME/DME/IRU or GPS.
RADAR required.

TILLT
16000
*5100
126°
(33)
ZIPRR
6000
*5100
134°
(25)
WURLL
6000
*5100
134°
(44)
TCUPS
FL260 280K
6000
*4700
109°
(21)
RUKKI
FL210
108°
(22)
SCANN
109°
(16)
BAUBB
13000
11000
(16)
089°
099°
(29)
STYFF
9000
080°
(7)
KAYNN
7000
057°
(8)
LAXBB
5000 200K
044°
(14)
KLEVR
5000 200K
Ldg Rwy 20R
016°
SAGER
JJAWS
6000
092°
(9)
PUZZL
5000 220K
017°
(10)
MINOE
3000 210K
Ldg Rwy 2L
N

NOTE: Expect Rwy 20R unless otherwise assigned by ATC.

NOTE: Chart not to scale.