HCF APPROACH
NORTH 120.2 322.4
SOUTH 119.5 225.4
ATIS
128.6
CLNC DEL
120.6 290.5
GND CON
121.9 279.6
MAUI TOWER ★
118.7 (CTAF) 279.6

TOP ALTITUDE: 7000



NOTE: DME required.

TAKEOFF MINIMUMS
Rwy 23: NA- obstacles and ATC.
Rwy 2: Standard with ATC climb of 480′ per NM to 2200.
Rwy 5: Standard with ATC climb of 480′ per NM to 2900.
Rwy 20: Standard with minimum climb of 480′ per NM to 7000.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb on heading 024° to 2100 then climbing right turn to 7000 to ONOHI/OGG 23 DME via heading 115° and OGG R-085.

TAKEOFF RUNWAY 5: Climbing left turn on heading 024° to 2100 then climbing right turn to 7000 to ONOHI/OGG 23 DME via heading 115° and OGG R-085.

TAKEOFF RUNWAY 20: Climb on heading 204° to 2100 then climbing left turn to 7000 to ONOHI/OGG 23 DME via direct OGG VORTAC and OGG R-085.

BARBY TRANSITION (ONOHI2.BARBY): From over ONOHI/OGG 23 DME on OGG R-085 to BARBY/OGG 25 DME.

PAC, 29 OCT 2026 to 24 DEC 2026
PAC, 29 OCT 2026 to 24 DEC 2026